


GEVULKANISEERDE SPANKOPPEN



A = Uitvoering	
L	glad
R	met radiale groef
S	met radiale en axiale groef
W	zacht/bewerkbaar

Type	Ref./Art.	L	D	●			⬢			■		
				A	stap		A	stap		A	stap	
32	32L	44	57,7	4-32	L	1	7-27	L	1	7-22	L	1
	32R	44	57,7	8-32	R	1	8-27	R	1	8-22	R	1
	32S	44	57,7	11-32	S	1						
	32EM	44	57,7	4-32	W	1						

Type	Ref./Art.	L	Ref./Art.	L	D	●			⬢			■		
						A	stap		A	stap		A	stap	
42	42L	42			79,3	4-42	L	1	7-38	L	1	7-30	L	1
	42R	42	42BR	47	79,3	8-42	R	1	8-38	R	1	8-30	R	1
	42S	42	42BS	47	79,3	11-42	S	1						
	42EM	42			79,3	4-42	W	1						

Voor Index MS 42 kan men Ref. 42B gebruiken

Type	Ref./Art.	L	D	●			⬢			■		
				A	stap		A	stap		A	stap	
52	52L	46	79,3	4-52	L	1	7-45	L	1	7-36	L	1
	52R	46	79,3	8-52	R	1	8-45	R	1	8-36	R	1
	52S	46	79,3	11-52	S	1						
	52EM	46	79,3	4-52	W	1						

Type	Ref./Art.	L	Ref./Art.	L	D	●			⬢			■		
						A	stap		A	stap		A	stap	
65	65L	53			99,5	4-65	L	1	7-56	L	1	7-46		
	65R	53	65BR	58	99,5	8-65	R	1	8-56	R	1	8-46		
	65S	53	65BS	58	99,5	11-65	S	1						
	65EM	53			99,5	4-65	W	1						

Voor Index MS 52 kan men Ref. 65B gebruiken

Type	Ref./Art.	L	D	●			⬢			■		
				A	stap		A	stap		A	stap	
80	80L	53	114,5	4-80	L	1	7-68	L	1	7-56	L	1
	80R	53	114,5	8-80	R	1	8-68	R	1	8-56	R	1
	80S	53	114,5	11-80	S	1						
	80EM	53	114,5	4-80	W	1						

Spanbereik: +/- 0.30

afmetingen in mm